

CLIPPEDIMAGE= JP360177568A

PAT-NO: JP360177568A

DOCUMENT-IDENTIFIER: JP 60177568 A

TITLE: FUEL CELL POWER GENERATING SYSTEM

PUBN-DATE: September 11, 1985

INVENTOR-INFORMATION:

NAME

NAKAYAMA, TAESUKE

ASSIGNEE-INFORMATION:

NAME

MITSUBISHI ELECTRIC CORP

COUNTRY

N/A

APPL-NO: JP59034547

APPL-DATE: February 23, 1984

INT-CL (IPC): H01M008/04

US-CL-CURRENT: 429/26,429/46

ABSTRACT:

PURPOSE: To keep phosphoric acid of electrolyte to higher temperature than its freezing point by covering the outer surface of fuel cell main body with heat insulating material and arranging a heater in the fuel cell main body.

CONSTITUTION: Four heaters 7 arranged so as to surround four sides of a cooler 4 are connected in series with a wire 8, and connected to a power source 9 arranged outside a fuel cell main body 5. When the fuel cell 5 is transported or installed, valves 4b and 4c are demounted from a cooling medium supply source, and hot water having a specified temperature is filled and valves 4b and 4c are closed. When the power source is turned on, four heaters are heated and temperature reaches a specified value, and the power source is turned off. When the temperature inside the fuel cell 5 is decreased with

the time elapsed,
the power source is turned on. Therefore, phosphoric acid
solution is always
kept to higher temperature than its freezing point.

COPYRIGHT: (C)1985,JPO&Japio